

FLOOR, WALL & MOSAIC

CASTLEGATE™
GLAZED PORCELAIN & GLAZED CERAMIC



Photo features Castlegate Gray 18 x 18 on the floor with Gray 9 x 12 and Universal 2 x 2 mosaic on the backsplash.

CASTLEGATE™ GLAZED PORCELAIN FLOOR AND GLAZED CERAMIC WALL & MOSAIC

Inspired by natural stone, Castlegate™ provides a rustic visual in three warm colors. The porcelain floor tile, offered with a coordinating ceramic wall and mosaic tile, work beautifully together in both residential and light commercial installations.

CASTLEGATE™

GLAZED PORCELAIN FLOOR TILE



BEIGE CG15



GRAY CG16



BROWN CG17

GLAZED CERAMIC WALL TILE



BEIGE CG15



GRAY CG16



BROWN CG17

GLAZED CERAMIC MOSAIC



UNIVERSAL CG18 (available in blend only)





FLOOR, WALL & MOSAIC







AMERICAN OLEAN®
PROVEN IN TILE™

Photo features Castlegate™ Gray 9 x 12 and Universal 2 x 2 mosaic on the backsplash.

SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	18 x 18 Floor Tile	17-3/4" x 17-3/4" (45.20 cm x 45.20 cm)	5/16"	18.00	8
	12 x 12 Floor Tile	11-13/16" x 11-13/16" (30.00 cm x 30.00 cm)	5/16"	15.00	15
	9 x 12 Wall Tile <input type="checkbox"/>	9" x 12" (22.91 cm x 30.54 cm)	5/16"	11.25	15
	2 x 2 Mosaic <input type="checkbox"/> <input type="checkbox"/>	12" x 24" Sheet (30.48 cm x 60.96 cm Sheet)	1/4"	24.00	12

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose	3 x 12	P-43C9	30
	Wall Bullnose (9" side) <input type="checkbox"/>	3 x 9	S-4309	54
	Wall Bullnose Corner <input type="checkbox"/>	3 x 3	SN-4309	32
	Mosaic Bullnose <input type="checkbox"/>	2 x 2	S-886	108

Ceramic body Dot-mounted

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:

Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length of 15" or greater in a staggered brick-joint pattern.)

Wall: 1/16"

Mosaic: 1/8"

RELATIVE PRICING: Low

SHADE VARIATION



HIGH
(V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT	WALL RESULT	MOSAIC RESULT
Water Absorption	C373	< 0.5%	< 20.0%	< 3.0%
Breaking Strength	C648	> 275 lbs.	120 - 230 lbs.	> 250 lbs.
Scratch Hardness	MOHS	8.0	4.0 - 6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant
Abrasion Resistance	C1027	4	N/A	4

For additional information on test results, visit us at: americanolean.com/information/TestResults.

USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●*
Wet & Level – Interior Floor	≥ 0.42	●*
Shower Floors (Residential or Light Commercial)	≥ 0.42	●**
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●*
Pool Linings	N/A	●**

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Floor tile suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

Wall and mosaic tile suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

* Wall tile not suitable for this application

** Mosaic tile only

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit americanolean.com.