

# PERSUADE™

## GLAZED PORCELAIN FLOOR WITH GLAZED CERAMIC WALL & MOSAIC

REVEAL IMAGING®

### GLAZED PORCELAIN FLOOR TILE



**PS40** White



**PS41** Beige



**PS42** Gray

### GLAZED CERAMIC WALL TILE



**PS40** White



**PS41** Beige



**PS42** Gray

### GLAZED CERAMIC 1 x 3 BRICK-JOINT MOSAIC 12 x 12 SHEET



**PS40** White



**PS41** Beige







**PS42** Gray

### USAGE

Floors	Walls	Countertops
F	W	C

**SIZES**

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	12 x 24 Floor Tile	(11-13/16" x 23-13/16") (30.00 cm x 60.48 cm)	5/16"	17.37	9
	6 x 18 Wall Tile	(6" x 18") (15.25 cm x 45.76 cm)	3/8"	11.25	15
	4 x 12 Wall Tile	(4-1/4" x 12-7/8") (10.91 cm x 32.77 cm)	5/16"	10.64	28
	1 x 3 Brick-Joint Mosaic (Dot-Mounted)	(12-1/4" x 12-1/8") (31.12 cm x 30.80 cm)	1/4"	10.56	12

**APPLICATIONS**

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	■*
Wet & Level - Interior Floor	≥ 0.42	■*
Shower Floors (Residential or Light Commercial)	≥ 0.42	■**
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■*
Pool Linings	N/A	■**

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit [marazzitile.com/DCOF](http://marazzitile.com/DCOF).

**APPLICATION NOTES:**

Floor tile suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

Wall and mosaic tile suitable for exterior applications in non-freezing climates, when proper installation methods are followed.



\* Wall tile not suitable for this application.

\*\* Mosaic tile only



All or select items within this series meet the requirements for these qualifications. For more information visit [marazzitile.com](http://marazzitile.com).

**TRIM**

Description	Number	Size	Shape
Floor Bullnose	P-43F9	3 x 24	
Jolly	S1/212J	1/2 x 12	

**INSTALLATION**

Grout Joint Recommendation	Shade Variation
<p><b>Floor:</b> 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)</p> <p><b>6 x 18 Wall:</b> 1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%.)</p> <p><b>4 x 12 Wall:</b> 1/16" (When rectangular size is installed in a staggered brick-joint pattern, overlap should not exceed 33%.)</p> <p><b>Mosaic:</b> 1/8"</p>	<p><b>V2</b> Medium Variation</p>

**PERFORMANCE CHARACTERISTICS**

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	<0.5%	<20.0%	<3.0%
Breaking Strength	C648	> 275 lbs	120 - 230 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	4.0 - 6.0	7.0
Chemical Resistance	C650	Resistant	Resistant	Resistant
Abrasion Resistance	C1027	III	N/A	III

For additional information on test results, visit us at: [marazzitile.com/information/TestResults](http://marazzitile.com/information/TestResults).

**NOTES**

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [marazzitile.com/Factors](http://marazzitile.com/Factors).

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [marazzitile.com/LargeTiles](http://marazzitile.com/LargeTiles) for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit [marazzitile.com](http://marazzitile.com).