

FLOOR

# HISTORIC BRIDGE™

GLAZED PORCELAIN



# HISTORIC BRIDGE™ GLAZED PORCELAIN FLOOR WITH REVEAL IMAGING®

Historic Bridge™ perfectly captures the look of exposed and weathered wood, with authentic details like water staining and cracking to worn-paint effects. Four rich colors feature a high level of variance. Special glazing adds to the genuine effect by creating a slight sheen along the graining. All colors are available in a plank size well-suited for creating floors with a rustic look. Historic Bridge answers current demand for organic influences from residential to commercial settings.

HISTORIC BRIDGE™

## GLAZED PORCELAIN FLOOR TILE



UPPER FERRY HB01



BANK'S BRIDGE HB03



OLD HOLLOW HB02



OLD FORGE HB04



All or select items within this series meet the requirements for these qualifications. For more information visit [americanolean.com](http://americanolean.com).


AMERICANOLEAN.COM




Photo features Historic Bridge™ Upper Ferry 6 x 36 on the floor.



SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	6 x 36 Floor Tile	5-7/8" x 35-7/16" (15.00 cm x 90.00 cm)	5/16"	13.05	9

TRIM

			NUMBER	PIECES/ CARTON
	Floor Bullnose	3 x 18	S-43H9	16

INSTALLATION & PRICING

RECOMMENDED GROUT JOINT:

Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)

RELATIVE PRICING: Medium to High

SHADE VARIATION



PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	3

For additional information on test results, visit us at: [americanolean.com/information/TestResults](http://americanolean.com/information/TestResults).

USAGE

FLOORS	WALLS	COUNTERTOPS
F	W	C

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [americanolean.com/DCOF](http://americanolean.com/DCOF).

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [americanolean.com/Factors](http://americanolean.com/Factors).

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [americanolean.com/LargeTiles](http://americanolean.com/LargeTiles) for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit [americanolean.com](http://americanolean.com).